

Q. When does my Saab need an engine oil change? A. Every 5000 miles or once a year, whichever comes first

Q. What kind of oil do I use and how much does it A. Use the chart below to find the recommended oil (**highlighted in BLUE**) and quantity for your

Q. What Oil Filter do I use and do I need anything A. Use the chart below to find your parts for your model. Click on the hyperlink to buy.

MODEL	YEAR		Recommended Oil Type	Recommended Viscosity	Oil Quantity	Oil Filter Part Number	Associated Parts	Service Interval
C900	1979-1993 incl 1994 Convertible	B201, B202, B212	Conventional, Semi or Full Synthetic 10W-30	API SJ, CCMC G4/G5, SAE 10W-30 , 10W-40, 5W-30, 5W-40, 15W-40 may be used except in cold weather	4.5 Qts	93186554 4-Cyl	9132929 Drain Plug	Every 5000 miles or once a year, whichever comes first
							9132937 Gasket- Oil Drain plug	
9000	1986-1989	B202	Conventional, Semi or Full Synthetic 10W-30	API SJ, CCMC G4/G5, SAE 10W-30 , 10W-40, 5W-30, 5W-40, 15W-40 may be used except in cold weather	4.5 Qts	93186554 4-Cyl	7563042 Drain Plug	Every 5000 miles or once a year, whichever comes first
							7522709 Gasket	
9000CS	1990-1998	B234, B308i	Full Synthetic 10W-30	API SJ, CCMC G4/G5, SAE 10W-30 , 10W-40, 5W-30, 5W-40, 15W-40 may be used except in cold weather. For areas with temp above 60°F 15W- 50 or 20W-50 may be used.	4Cyl 4.2Qts	93186554 4-Cyl	7563042 Drain Plug	Every 5000 miles or once a year, whichever comes first
					6Cyl 4.7Qts		6Cyl 93178952	
		90409376 Drain Plug						
				11016282 Gasket- Oil Drain plug				
NG 900	1994-1998			B204, B234, B258	Full Synthetic 10W-30	API SJ, CCMC G4/G5, SAE 10W-30 , 10W-40, 5W-30, 5W-40, 15W-40 may be used except in cold weather. For areas with temp above 60°F 15W- 50 or 20W-50 may be used.	4Cyl 4.2Qts	93186554 4-Cyl
		6Cyl 4.7Qts	6Cyl 93178952				9132937 Gasket- Oil Drain plug	
				90409376 Drain Plug				
				11016282 Gasket- Oil Drain plug				

9-3	1999-2002 incl 2003 Convertible	B204, B205, B235	Full Synthetic 0W-40	API SJ, CCMC G4/G5, SAE 5W-30, 0W-30, 5W-40, ILSAC GF-3 specification is approved for use in applicable markets. Oils with viscosity's 0W-40 /0W-50 of well known brands and fulfilling minimum	4.2 Qts	93186554 4-Cyl	9132929 Drain Plug 9132937 Gasket- Oil Drain plug	Every 5000 miles or once a year, whichever comes first
9-5	1999-2009	B235, B308t	Full Synthetic 0W-40	API SM or higher, GM-LL-A-025, ACEA A3/B3, SAE 0W-30, 0W-40, 5W-30 or 0W-40	4Cyl 4.2Qts 6Cyl 4.6Qts	93186554 All Engines	9132929 Drain Plug 9132937 Gasket- Oil Drain plug	Every 5000 miles or once a year, whichever comes first
9-3 SS	2003-2011	B207, B284	Full Synthetic 0W-40	API SM or higher, GM-LL-A-025, ACEA A3/B3, SAE 0W-30, 0W-40, 5W-30 or 0W-40	4Cyl 6.3Qts 6Cyl 6.0Qts	4Cyl 12605566 6Cyl 93186310	11562588 Drain Plug 3536966 Gasket- Oil Drain plug 12580255 Oil Filter Housing O-ring 9132929 Drain Plug 12616850 Gasket- Oil Drain plug 12577653 Oil Filter O-ring included with Filter	Every 5000 miles or once a year, whichever comes first
9-2X	2005-2006	EJ205, EJ253, EJ255	Full Synthetic 5W-30	API SM, ILSAC GF-4 or higher SAE 5W-30 For areas with very high temperatures or used for heavy-duty applications SAE 30, 40, 10W-50, 20W-	4.2 Qts	32009814	32008482 Drain Plug 32005452 Gasket- Oil Drain plug	Every 5000 miles or once a year, whichever comes first
9-7X	2005-2009	LL8 = 4.2L Inline 6 LH6 = 5.3L V8, LS2 =	Full Synthetic 5W-30	LL8/LH6 - GM6094M SAE 5W-30 API SM. Below 20°F use SAE 5W-30 or SAE 0W-30 synthetic oil. LS2 - 6.0 Liter V8 GM4718M Mobil 1	LL8 6Cyl 7Qts LH6/LS2	LL8 6Cyl 19210285 LH6/LS2 V8	11562588 Drain Plug Oil Gasket Only comes with drain plug 11562588 Drain Plug	Every 5000 miles or once a year, whichever comes first

		6.0L V8		Synthetic 5W-30	V8 6Qts	19303975	Oil Gasket Only comes with drain plug	
NG 9-5	2010-2011	A20NHT 4 Cyl, A28NER V6	Full Synthetic 5W-30 Annual Protect	dexos1™ Gen 2 GM4718M ACEA A3/B4 API SN SAE 5W-30 , 5W-40, 0W-30 or 0W-40	4Cyl 6.3Qts	4Cyl 12605566	11562588 Drain Plug 3536966 Gasket-Oil Drain plug	Every 5000 miles or once a year, whichever comes first
					6Cyl 6.6Qts	6 Cyl 93186310	11562588 Drain Plug 12577653 Oil Filter O-ring included with Filter 12616850 Gasket-Oil Drain plug	
9-4X	2011	A28NER 2.8 V6-T, A30YH 3.0 V6i	Full Synthetic 5W-30 Annual Protect	dexos1™ Gen 2 GM4718M ACEA A3/B4 API SN SAE 5W-30 , 5W-40, 0W-30 or 0W-40	A28NER 6 Qts	A28NER 93186310	11562588 Drain Plug O-ring included with Filter 93186310 12616850 Gasket-Oil Drain plug	Every 5000 miles or once a year, whichever comes first
					A30YH 6 Qts	A30YH 89017525	11562588 Drain Plug 12616850 Gasket-Oil Drain plug	

Orio proudly recommends Mobil One Synthetic oil